

COMPACT DOSING STATIONS



OVERVIEW

- Standardized dosing tanks
- Space-saving wall mounting
- Wide range of applications
- High safety standard
- High quality materials
- Easy to operate
- Low maintenance
- Complete range of accessories


TECHNICAL DATA

UNIT DATA		CTD - ...						
		.. 40.1	.. 75.1	.. 100.1	.. 200.1	.. 300.1	.. 500.1	.. 1000.1
Tank volume	Litres	40	75	100	200	300	500	1.000
Flow capacity	l/h	0,4...35	0,4...180	0,4...180	0,4...570	0,4...570	0,4...570	0,4...570
Permissible counterpressure	bar (max)	10	10	10	10	10	10	10
Nominal width of suction lance	DN	5	5/10	5/10	5/10/15	5/10/15	5/10/15	5/10/15

ALLOCATION OF DOSING PUMPS

PUMP SERIES	CTD-40.1	CTD-75.1 ... CTD-1000.1
Solenoid diaphragm pumps 	C204.1-2,4e C204.1-7,0e C204.1-10e C204.1-35e	C204.1-2,4e C204.1-7,0e C204.1-10e C204.1-35e
Stepper motor diaphragm pumps 	X	iSTEP S 20 iSTEP S 30 iSTEP S 40 iSTEP S 50
Diaphragm pumps 	X	C409.2-25 Pro+ ... C409.2-350e Pro+ RF409.2-75e ... RF 409.2-350e C410.2-280e ... C410.2-570e RF410.2-280e ... RF410.2-570e
Multi-layer diaphragm pumps 	X	C409.2-11 ML Pro+ ... C409.2-220 ML Pro+ RF409.2-11 ML ... RF409.2-220 ML C410.2-500 ML RF410.2-135 ML ... RF410.2-500 ML

DIMENSIONS



	D	A	B	H
CTD - 40.1	420	70	70	425
CTD - 75.1	460	70	70	600
CTD - 100.1	460	70	70	760
CTD - 200.1	670	80	100	750
CTD - 300.1	670	80	100	1.030
CTD - 500.1	790	90	90	1.170
CTD - 1000.1	1080	110	100	1.290

BASIC DESIGNS

CTD

Dosing tank (PE-transparent) with litre scale and cover (DIN162)

Suction lance with foot valve and sieve

Ventilation- / exhaust bow with hose nozzle

Brackets for floor mounting

Type	Preis (EUR)
CTD - 40.1	Ⓢ
CTD - 75.1	Ⓢ
CTD - 100.1	Ⓢ
CTD - 200.1	Ⓢ
CTD - 300.1	Ⓢ
CTD - 500.1	Ⓢ
CTD - 1000.1	Ⓢ