

Lutz Pump Sets

0.3 Pump Set B2 Battery (polyvinylidene flouride)

such as chloric acid, chromic acid, sulphuric acid, nitric acid, hydrofluoric acid and sodium hypochlorite.

For removing small quantities from hobbocks, canisters and drums.

- **Motor B2 Battery,**
260 Watt internally ventilated

Density (kg/dm ³)	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1.6	400	80 (45)	8

Max. temperature of medium 90 °C

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil. When using a nozzle the delivery rate is reduced to approximate values (information in the brackets).



Pump Set B2 Battery

for acids and alkalis



For emptying canisters and drums	Pump B2 Battery PVDF 32-R SL			Set B2 Battery PVDF 32-R SL			Set B2 Battery PVDF 32-R SL with flow meter TR3-PVDF
	Motor B2 Battery	✓			✓		
Flow meter TR3-PVDF	-			-			✓
Pump tube PVDF 32-R-SL	✓			✓			✓
1,5 m special chemical hose 3/4"	-			✓			✓
Hose connectors 3/4"	✓			✓			✓
Hose clamps	-			✓			✓
Nozzle PVDF	-			✓			✓
Immersion depth	500 mm	700 mm	1000 mm	500 mm	700 mm	1000 mm	1000 mm
Order No.	0207-109	0207-110	0207-111	0207-080	0207-081	0207-082	0207-083
Battery 21,6 V				0332-026			
Battery charger				0335-335			