




Accessories

Product detail	Specification	Order No.
	<p>Trolley for horizontal eccentric screw pump B70H For mobile use of B70. With fixing material to assemble the motor.</p> <p>Material: Stainless steel (1.4571) Dimensions trolley 820 x 520 x 940 mm</p> <p>Trolley</p> <p>Trolley with electrically conductive wheels</p> <p>Additional price trolley for ex motor protection switch (Order motor protection switch separately)</p>	<p>0208-194</p> <p>0208-195 ●</p> <p>0208-198 ●</p>
	<p>Motor protective switch for motor B70H Explosion proof according to EEx de IIC T6 with thermal and electromagnetic trip, protection type IP 66.</p> <p>Ex, 2.5 - 4.0 A for B70H (Ex)</p>	<p>0335-419 ●</p>
	<p>PVC spiral hose, fabric reinforced Hose for food liquids made of PVC, with woven layer and imbedded galvanized steel helix, inside and outside smooth, complies with EU-regulations 10/2011 and 1935/2004.</p> <p>Operating pressure: max. 14 bar Temperature of liquid: -5 up to +65 °C Nominal diameter: Weight: DN 38 (1 1/2") 1.15 kg/m DN 50 (2") 1.60 kg/m</p>	<p>0374-469</p> <p>0374-470</p>
	<p>Universal chemical hose Colour coding: "blue/white/blue". Suitable for food and luxury foodstuffs, pharmaceuticals, cosmetics and hygiene products Conform to FDA and USP class VI. Complies with EU-regulations 10/2011 and 1935/2004. Internal finish: UPE light with spiraled OHM conductive stripes UPE black, smooth, non-bleeding, abrasion-resistant. Intermediate layer: EPDM conductive complies with the requirements of the recommendation XXI category 2 of the BfR and FDA standards. External finish: EPDM light grey, conductive, non-bleeding, ozone- and UV resistant, hardly flammable, (starting from DN 25 with galvanized steel helix, suitable as suction and pressure hose). Electrically conductive: Type Ω/T (<10⁶ Ohm between the fittings, <10⁹ Ohm through the hose wall) according to DIN EN 12115:2011.</p> <p>Operating pressure: max. 16 bar Temperature of liquid: -30 up to +100 °C (dependant on the liquid), can be sterilized at 130°C for 30 minutes (open system)</p> <p>Nominal diameter: Weight: DN 38 (1 1/2") 1.2 kg/m DN 50 (2") 1.9 kg/m</p>	<p>0374-478 ●</p> <p>0374-479 ●</p>

● Suitable for transferring flammable and easy flammable liquids (e.g. Ethanol, petrol) or in explosive hazard area.

Specification	Order No.	Product detail									
<p>Hose clips</p> <p>Stainless steel hose clips with threaded screw for fixing hoses of various nominal bore at the hose connection.</p> <p>Nominal diameter: DN 32 - 38 (1 1/4" - 1 1/2") DN 50 (2")</p>	<p>0302-402 0302-403</p>										
<p>Hose connection with Tri-clamp</p> <p>For connecting the hose to the eccentric screw pump B70, discharge spout or Tri-Clamp armatures (comprising a hose connection, locking clamp and seal)</p> <p>Material: Stainless steel (1.4404)</p> <table border="0"> <tr> <td>Connection:</td> <td>for hose nominal diameter:</td> <td>Seal:</td> </tr> <tr> <td>Tri-Clamp DN 50</td> <td>DN 38 (1 1/2")</td> <td>FPM</td> </tr> <tr> <td>Tri-Clamp DN 50</td> <td>DN 50 (2")</td> <td>FPM</td> </tr> </table> <p>Please note: The assembler is responsible for the professional fixing of the hose according to the current Pressure Equipment Directive.</p>	Connection:	for hose nominal diameter:	Seal:	Tri-Clamp DN 50	DN 38 (1 1/2")	FPM	Tri-Clamp DN 50	DN 50 (2")	FPM	<p>0204-878 0204-880</p>	
Connection:	for hose nominal diameter:	Seal:									
Tri-Clamp DN 50	DN 38 (1 1/2")	FPM									
Tri-Clamp DN 50	DN 50 (2")	FPM									
<p>Hose connector with Tri-clamp</p> <p>For connection of conductive hose onto the eccentric screw pump B70, discharge spout or Tri-Clamp armatures in explosive hazardous area. The hose connector ensures a highly conduction transition between conductive hose and pump/armature.</p> <p>The ohmic resistance between the armatures must be lower than 10⁶ Ohm. (Consisting of hose connector, clamp collars, locking clamp and seal)</p> <p>Material: Stainless steel (1.4404)</p> <table border="0"> <tr> <td>Connection:</td> <td>for hose Nominal diameter:</td> <td>Seal:</td> </tr> <tr> <td>Tri-Clamp DN 50</td> <td>DN 50 (2")</td> <td>FPM</td> </tr> </table>	Connection:	for hose Nominal diameter:	Seal:	Tri-Clamp DN 50	DN 50 (2")	FPM	<p>0204-869 ●</p>				
Connection:	for hose Nominal diameter:	Seal:									
Tri-Clamp DN 50	DN 50 (2")	FPM									

Further accessories can be found in our eccentric screw pump leaflet or on request.

